

# VOSS AUDIO CP15A+ASC4-4 ACTIVE COLUMN SPEAKER

## PA SYSTEM



Applications: Banquet halls, multi-purpose halls, conference rooms, churches, small mobile performances, music bars, weddings and other indoor and outdoor sound reinforcement places.

- By a 15-inch 100-core 220-magnet bass plus two 4 × 4-inch 26-core neodymium magnetic full-range unit composed of high sound pressure level active sound post system;
- All-weather outdoor waterproof design, the Column Speaker is protected by aluminium shell, the bass cabinet is sprayed with polyurea, with high corrosion resistance and high durability, can maintain its beautiful appearance and excellent sound performance in a variety of environments. The system is especially designed for front inverted multi-functional structure, **easy to dismantle and install!** The column speaker and accessories can be stored in the body of the subwoofer. The overall is light-weight and compact, and the bottom is equipped with high-quality casters, easy to carry, push and go.

- Multiple input design: Support Bluetooth, USB, AUX, balanced and unbalanced line input, microphone input.
- Full-range and subwoofer independent adjustment, simple and convenient. Full-range support 10dB increase/decrease adjustments in the upper and lower midrange, low cut frequency adjustment, volume independent adjustment; Subwoofer has high cut, phase, BASS, volume independent adjustment.
- Powerful protection circuit design, protection functions are DC, overheating, overload and limiting.
- With a wide coverage angle, the sound quality is clear, full and transparent, with excellent music performance.
- System Type: Active Speaker

-Crossover mode: 2-way frequency, crossover frequency adjustable.

-Frequency Response: 35Hz~18kHz(-10dB)

-Speaker rated power: 500W/8Ω+400W/4Ω

-Active module rated power: 800W+800W@8Ω

-Maximum SPL: 121dB/127dB (Peak)

-Total Harmonic Distortion: < 1% -Directivity: H130°×V30

Bass Configuration: 15' 100-core voice coil 220 magnet woofer

-Post configuration: 4.inch 26-core neodymium magnetic full-range unit × 8PCS

-Power supply voltage: 220~240VAC

-Input socket: USB, AUX, XLR composite interface (XLR balanced or 6.35MM)

-Full-range input: 1+ 1- -Full-range connector: SpeakCON NL4

-Cabinet Material: High-end birch plywood

-Finish: Spray Polyurethane Waterproofing Coating + aluminium alloy column speaker

-Surface grille material: Mild steel

-Cabinet size: 470×620×540mm (Subwoofer cabinet)

-Cabinet size: 125×140×495mm (Column speaker cabinet)

-Weight: 52.5 KG / SET